

## Innovative

- Trendy streamline design
- One-step installation
- Activated by NFC
- Provide smart App as a charging partner

## Compatibility

- Type 1 connector for American market
- Interoperable with all major automobiles in North American market
- OCPP 1.6 Json standard protocol

## Secure and safe

- Anti-welding protection
- NEMA4(IP66)dustproof and waterproof design
- CCID 20 leakage current protection
- UL listed and certified with the highest standards for electrical safety

# cWatt9.6



**Model:PhG-C9K6A/G2NA-E**

Datasheet	Model	cWatt9.6AU	cWatt9.6GU
<b>Input</b>	Power Supply	1P+N+PE	
	Rated Voltage	240V AC	
	Rated Current	40A	
	Frequency	60Hz	
	Plug	NEMA 14-50P	NEMA 6-50P
<b>Output</b>	Charge Outlet	Type 1	
	Output Power	9.6kW	
<b>User Interface</b>	Charge Connector	Type 2 Cable/Type 2 Socket	
	Cable Length	7.5m(25 Feet)	
	Housing Material	PC	
	LED Indicator	Green/Yellow/Red	
	RFID Reader	Mifare ISO/IEC14443A	
	Start Mode	Plug&Play/RFID Card/NFC/App	
<b>Communication</b>	Wi-Fi	Yes	
	Bluetooth	Yes	
	Ethernet	Yes	
<b>Safety</b>	Leakag Current Protection	CCID20	
	Enclosure Rating	NEMA 4	
	Impact Protection	IK10	
	Electrical Protection	Over current protection, Residual current protection, Short circuit protection, Surge protection, Over/Under voltage protection, Over/Under frequency protection, Over/Under temperature protection	
	Certification	CULUS/FCC/Energy Star/BQB	
	Certification Standard	UL2594 UL2231-11-21 FCC Part15B	
	Warranty	2 Years	
<b>Environment</b>	Installation	Wall-mount/Pole-mount(Optional)	
	Work Temperature	-30°C~+50°C	
	Work Humidity	5%-95%	
	Work Altitude	<2000m	
<b>Package</b>	Product Dimension	344*192*100mm(H*W*D)	
	Package Dimension	430*330*315mm(H*W*D)	
	Net Weight	6kg	
	Gross Weight	8kg	
	External Package	Carton	